

GSE Nonwoven Geotextiles

GSE Nonwoven Geotextiles are a family of staple fiber needlepunched geotextiles. The geotextiles are manufactured using an advanced manufacturing and quality system to produce the most uniform and consistent nonwoven needlepunched geotextile currently available in the industry. GSE combines a fiber selection and approval system with an in-line quality control and a state-of-the-art laboratory to ensure that every roll shipped meets customer specifications.



AT THE CORE:
A family of geotextiles used for separation, filtration, protection and drainage applications.

Product Specifications

These product specifications meet GRI GT12, GRI GT13 and AASHTO M288

Tested Property ⁽¹⁾	Test Method	Frequency	Minimum Average Roll Value					
			NW4	NW6	NW8	NW10	NW12	NW16
AASHTO M288 Class			3	2	1	>1	>>1	>>>1
Mass per Unit Area, oz/yd ²	ASTM D 5261	90,000 ft ²	4	6	8	10	12	16
Grab Tensile Strength, lb	ASTM D 4632	90,000 ft ²	120	160	220	260	320	390
Grab Elongation, %	ASTM D 4632	90,000 ft ²	50	50	50	50	50	50
CBR Puncture Strength, lb	ASTM D 6241	540,000 ft ²	303	435	575	725	925	1,125
Trapezoidal Tear Strength, lb	ASTM D 4533	90,000 ft ²	50	65	90	100	125	150
Apparent Opening Size, Sieve No. (mm)	ASTM D 4751	540,000 ft ²	70 (0.212)	70 (0.212)	80 (0.180)	100 (0.150)	100 (0.150)	100 (0.150)
Permittivity, sec ⁻¹	ASTM D 4491	540,000 ft ²	1.80	1.50	1.30	1.00	0.80	0.60
Water Flow Rate, gpm/ft ²	ASTM D 4491	540,000 ft ²	135	110	95	75	60	45
UV Resistance % retained after 500 hours	ASTM D 4355	per formulation		70	70	70	70	70
TYPICAL ROLL DIMENSIONS								
Roll Length ⁽²⁾ , ft			300	300	300	300	300	300
Roll Width ⁽²⁾ , ft			15	15	15	15	15	15
Roll Area, ft ²			4500	4500	4500	4500	4500	4500
Roll Area (yd ²)			500	500	500	500	500	500

NOTES:

- ⁽¹⁾The property values listed are in weaker principal direction. All values listed are Minimum Average Roll Values except apparent opening size in mm and UV resistance. Apparent opening size (mm) is a Maximum Average Roll Value. UV is a typical value.
- ⁽²⁾Roll lengths and widths have a tolerance of ±1%.

GSE is a leading manufacturer and marketer of geosynthetic lining products and services. We've built a reputation of reliability through our dedication to providing consistency of product, price and protection to our global customers.

Our commitment to innovation, our focus on quality and our industry expertise allow us the flexibility to collaborate with our clients to develop a custom, purpose-fit solution.



[DURABILITY RUNS DEEP] For more information on this product and others, please visit us at GSEworld.com, call 800.435.2008 or contact your local sales office.