


# GSE Geosynthetic Storage Recommendations

## Geomembrane Storage


- A. Rolls of material shall be unloaded with equipment that will not damage the geomembrane.
- B. Fabric-straps, spreader bars or other approved equipment shall be used for handling rolls of geomembrane.
- C. Materials should be stored in a flat, dry and well drained area.
- D. The surface shall be free of sharp rocks or other objects that could damage the materials.
- E. Geomembrane rolls may be stacked up to 3 tiers high.
- F. Product segregation by item code and special roll length, upon delivery, is recommended.



[GSE Geomembrane]

## Geotextile and Geocomposite Storage

- A. Rolls of material shall be unloaded with equipment that will not damage the geocomposite.
- B. Fabric-straps, spreader bars, stinger bars, or other approved equipment shall be used for handling geotextile/geocomposite rolls.
- C. Materials should be stored in a flat, dry and well drained area.
- D. The surface shall be free of sharp rocks or other objects that could damage the materials.
- E. For extended storage (> 6 months), geotextile/geocomposite should be covered with protective waterproof tarps.
- F. Geotextile/geocomposite rolls may be stacked up to 3 tiers high.
- G. Product segregation by item code and special roll length, upon delivery, is recommended.



[GSE Geocomposite]

## GCL Storage

- A. Rolls of material shall be unloaded with equipment that will not damage the GCL.
- B. Fabric-straps, spreader bars, stinger bars, or other approved equipment shall be used for handling GCL rolls.
- C. Materials should be stored in a flat, dry and well drained area.
- D. The surface shall be free of sharp rocks or other objects that could damage the materials.
- E. GCL shall be covered with protective waterproof tarps.
- F. For extended storage (> 6 months) GCL should be stored inside a completely enclosed structure. Building temperature should not exceed 95 degrees
- G. The building must be well ventilated to avoid exposure to constant excessive humidity and condensation.
- H. The rolls should remain in their original, unopened, plastic wrapping to prevent undue hydration prior to installation. H. GCL material may be stacked up to 3 tiers high.
- I. Product segregation by item code and special roll length, upon delivery, is recommended.



[GSE GCL]

GSE is a leading manufacturer and marketer of geosynthetic lining products and services. We've built a reputation of reliability through our dedication to providing consistency of product, price and protection to our global customers.

Our commitment to innovation, our focus on quality and our industry expertise allow us the flexibility to collaborate with our clients to develop a custom, purpose-fit solution.

**[ DURABILITY RUNS DEEP ]** For more information on this product and others, please visit us at [GSEworld.com](http://GSEworld.com), call 800.435.2008 or contact your local sales office.

